



GP MINI crawler excavator (3.5-4ton)

Parameter

1	型号 model	WE35	WE40
2	铲斗容量 Bucket capacity	0.12m ³	0.15m ³
4	履带总长 Total track length mm	2150	2175
5	最小离地间隙 Minimum ground clearance mm	250	270
6	底盘宽度 Chassis width mm	1500	1500
7	履带宽度 Track width mm	300	300
9	全车高度 Full vehicle height mm	2375	2380
10	整机尺寸 Overall size mm	4180*1500*2380mm	4200*1500*2380mm
11	发动机型号 engine model	xinchai490	xinchai490
12	发动机功率 engine power	36.8kw	36.8kw
13	回转半径 Radius of gyration mm	1830	1840
14	挖掘高度 Digging height mm	3900	4450
15	卸载高度 Unloading height mm	2040	2050
16	挖掘深度 Digging depth mm	2800	2800
17	地面挖掘半径 Ground excavation radius mm	3860	3900
19	工作质量 operating weight	3680	4120
21	推土铲提升高度 Dozer blade lifting height mm	120	130
22	铲斗挖掘力 Bucket digging force	35KN	35KN
23	爬坡能力 Gradeability	35°	35°

NOTE:

1. The product is manufactured with Japanese Hitachi excavator technology;
2. This series is a MINI crawler excavator, suitable for use in small places such as homes, courtyards, gardens, and farmland;
3. The key components are imported parts: for example, the hydraulic motor is American EATON, the hydraulic multi-way valve is Japan Shimadzu, and the hydraulic oil seal is Japan NOK, etc.

